

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label) Glass Bead Blast Media			
MANUFACTURER'S NAME Maxi-Blast, Inc		EMERGENCY TELEPHONE NO. (574) 233-1161	
ADDRESS (Number, Street, City, State and Zip Code) 3650 North Olive Road, South Bend, Indiana 46628		MANUFACTURER'S D-U-N-S NO. 03-934-9162	
MATERIAL DESCRIPTION, PROPER SHIPPING NAME Glass Bead Item 86650 Class 55			
HAZARD CLASSES (as applicable) Non-Regulated			
CHEMICAL FAMILY Glass, Oxide		FORMULA Soda Lime Glass	

SECTION II – INGREDIENTS (list all ingredients)

CAS REGISTRY NO.	Approx. %W	CHEMICAL NAME(S)	Listed as a Carcinogen in NTP, IARC or OSHA 1910(z) (specify)
65997-17-3	100	Glass Oxide	No

SECTION III – PHYSICAL DATA

BOILING POINT ____ °F ____ °C	N.A.	SPECIFIC GRAVITY (H ₂ O=1)	2.4 - 2.5		
MELTING POINT ____ °F ____ °C	N.A.	PERCENT VOLATILE BY VOLUME (%)	N.A.	PERCENT SOLID BY WEIGHT (%)	100
VAPOR DENSITY (AIR=1)	N.A.	EVAPORATION RATE (=1)	N.A.		
SOLUBILITY IN WATER	Nil	PH=	N.A.		
APPEARANCE AND ODOR: Colorless Spheres, Odorless				MATERIAL FORM: Solid	

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Non Flammable	FLAMMABLE LIMITS	LEL N.A.	UEL N.A.
EXTINGUISHING MEDIA N.A.			
SPECIAL FIRE FIGHTING PROCEDURES N.A.			
UNUSUAL FIRE AND EXPLOSION HAZARDS N.A.			

SECTION V – HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE – Conditions to Avoid	THRESHOLD LIMIT VALUE <input type="text"/> PERMISSIBLE EXPOSURE LIMIT <input type="text"/>
Mechanical injury to eyes and/or skin can occur. Excessive dust inhalation may be harmful.	See Section IX.
PRIMARY ROUTES OF ENTRY <input checked="" type="checkbox"/> Inhalation <input checked="" type="checkbox"/> Skin Contact <input checked="" type="checkbox"/> Other (specify) Eye Through mechanical contact only.	
EMERGENCY AND FIRST AID PROCEDURES In case of irritation flush eyes or skin with water. In case of excessive inhalation of dust remove to fresh air. Call physician if necessary.	

SECTION VI – REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY(materials to avoid)		Hydrofluoric Acid	
HAZARDOUS DECOMPOSITION PRODUCTS		N.A.	
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID N.A.
	MAY NOT OCCUR	X	

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Caution – Spilled material may cause slippery floor conditions. Sweep or vacuum up and place waste in disposal container.	
WASTE DISPOSAL METHOD Disposal must be made according to Federal, State and Local regulations.	
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs) N.A.	
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33) N.A.	
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water) N.A.	
<input type="checkbox"/> Theoretical _____ lb/gal	<input type="checkbox"/> Analytical _____ lb/gal

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify Type) Provide adequate ventilation. NIOSH/MSHA approved respiratory protection as required.		
VENTILATION	LOCAL EXHAUST (Specify Rate) As required for specific user application.	SPECIAL
	MECHANICAL (General – Specify Rate) See Section IX "Other Precautions"	OTHER
PROTECTIVE GLOVES (Specify Type) Normal Work Gloves	EYE PROTECTION (Specify Type) Safety Goggles	
OTHER PROTECTIVE EQUIPMENT Special protection is required for workers exposed to abrasive blast operation.		

SECTION IX – SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING None
OTHER PRECAUTIONS Determine compliance with OSHA 1910.1000 Table Z-3 "Inert or Nuisance Dust"
PEL – Total Dust: 10 mg/m ³ Respirable Fraction: 5 mg/m ³
PEL = Permissible Exposure Limit, 8 hr. Time Weighted Average mg/m ³ = milligrams per cubic meter N.A. = Not Applicable

<p>Maxi-Blast[®] Inc.</p> <p>3650 North Olive Road – South Bend, In 46628 (574) 233-1161 – Fax: (574) 234-0792 – e-mail: info@maxiblast.com MSDSGB Page 2 Rev. – 6 1/31/08</p>	
---	--